


DCNM-FLSP Flush loudspeaker panel

DICENTIS



The Flush loudspeaker panel is intended for use in combination with the Flush base device (DCNM-FBD). It consists of a loudspeaker behind a grille. The loudspeaker produces excellent audio quality. The loudspeaker can even be active when the microphone is open to ensure the best possible audio experience for the delegates.

Functions

Interconnections

- 2 m (78.7 in) cable terminated with a 2 pole terminal block.

Parts included

Quantity	Component
1	DCNM-FLSP Flush loudspeaker panel

Technical specifications

Electrical

Frequency response (-3 dB) (Hz) (-3 dB at nominal level)	125 Hz – 15,000 Hz
Total harmonic distortion + noise (%)	0.10%
Nominal acoustic output level (dB SPL) (at 0.5 m)	72 dB SPL
Maximum acoustic output level (dB SPL)	87 dB SPL
Nominal impedance (Ω)	8 Ω / 2 W

- ▶ Stylish and modern design
- ▶ Excellent audio quality

Mechanical

Mounting type	Click-to-fit in a metal panel with a thickness of 2 mm, or in combination with the DCN-FCOUP Flush coupling and the DCNM-FEC Flush end cap in any surrounding
Dimensions (H x W x D) (mm)	74 mm x 100 mm x 31 mm
Dimensions (H x W x D) (in)	3 in x 4 in x 1.20 in
Weight (g)	175 g
Weight (lb)	0.40 lb
Color (RAL)	RAL 9017 Traffic black

Environmental

According to IEC 60721: storage (1K3), transportation (2K2) and operational (3K4).

Transportation temperature (°C)	-30 °C – 70 °C
Transportation temperature (°F)	-22 °F – 158 °F
Storage temperature (°C)	-5 °C – 45 °C
Storage temperature (°F)	23 °F – 113 °F
Operating relative humidity, non-condensing (%)	5% – 90%

Ordering information

DCNM-FLSP Flush loudspeaker panel

Flush mounted loudspeaker panel.

Order number **DCNM-FLSP | F.01U.383.840 Z.01X.001.902**

Services

EWE-DCNMFP-IW 12 mths wrty ext DICENTIS Flush Panel

12 months warranty extension

Order number **EWE-DCNMFP-IW | F.01U.406.171**



<https://www.keenfinity-group.com>